



VIDEO 5 LOGGER/4 HD VIDEO RECORDER

VIDEO 5 LOGGER HD is a powerful as run log recording tool, with multiple simultaneously video inputs.

Its flexibility allows to perform multiple tasks:

AUDIO/VIDEO Multiformat Recording up to 4 SD/HD channels.

24x7 recording, Legal copy.

Recording by time segment (user defined).

Recording with Watermark.

Recording with date and time.

Auto delete functions.

Automatic file deleting module configurable by date.

VGA Play module.

Recompression of recorded files.

Alerting system.

Audio Input: 8 Channels Per Input, Embedded in SD and HD.
Audio Output : 8 Channels Per Input, Embedded in SD and HD.

HD Format Support : 720p50, 720p59.94, 720p60, 1080PsF23.98, 1080p23.98, 1080PsF24, 1080p24, 1080PsF25, 1080p25, 1080PsF29.97, 1080p29.97, 1080PsF30, 1080p30, 1080i50, 1080i59.94 and 1080i60.

SUPPORTS MPEG 2 I-FRAME, DVCPROHD, MPEG2

etc.

Technical Specifications

4K, 3G, HD, SD, SDI & LTC I/O

12 bit 2K/HD/SD SDI I/O

12 bit internal processing

INPUT

4 for RECORDER SD/HD SDI
1 Genlock

OUTPUT

VGA

Dual Link 4:4:4, 4:4:4:4, 4:2:2:4 I/O

Single Link 4:2:2 I/O

16 Channels of embedded audio

Supported Video Modes

720x486i @ 59.94 Hz NTSC

720x576i @ 50.00 Hz PAL

1280x720p @ 23.976Hz, 24Hz, 25Hz,
29.97Hz, 30Hz, 50Hz, 59.94Hz, 60Hz

1920x1080i @ 47.96Hz, 48Hz, 50Hz,
59.94Hz, 60Hz

1920x1080PsF @ 23.976Hz, 24Hz,
25Hz, 29.97Hz, 30Hz

1920x1080p @ 23.976Hz, 24Hz, 25Hz,
29.97Hz, 30Hz, 47.96Hz, 48Hz, 50Hz,
59.94Hz, 60Hz

2048X1080p @ 23.976Hz, 24Hz, 25Hz,
29.97Hz, 30Hz, 47.96Hz, 48Hz, 50Hz,
59.94Hz, 60Hz

2048X1080i @ 47.96Hz, 48Hz, 50Hz,
59.94Hz, 60Hz

SMPTE specifications

12M, 125M, 259M, 272M, 274M, 291M,
292M, 296M, 299M, 372M, 424M, 425M



**For more information, please
visit our website**

MEDIA 5 S.R.L.

Paraná 425 - Piso 9 - Of B
(C1017AAI) Capital Federal
República Argentina

Phone: (+54 11) 4374 8386 / 8395

e-mail: info@video5.tv / web: www.video5.tv

USA: +1 305 735 3398

www.video5.tv